

GOLD TAPE



GOLD TAPE is made from high-density, 100% pure PTFE to ensure sealing in threaded connections. This provides several advantages compared to conventional PTFE tapes.

- 3 turns of wrapping are sufficient.
- Allows 180-degree reverse rotation.
- Does not bunch up, tear, or peel off.
- Does not break into pieces and clog lines.
- Can be used with oxygen.
- Retains its effectiveness even under vibration.
- Does not harden at high temperatures.
- Suitable for use with water, hot water, superheated water, steam, hot oil, compressed air, synthetic and mineral oils, all solvents, gases, and fuels.
- Compatible with all pneumatic and hydraulic fittings.

FEATURES:

- | | |
|----------------------|-----------------------------|
| - Thickness: | 0.2mm |
| - Width: | 12mm |
| - Length: | 10m |
| - Density: | 1.6 g/cm ³ |
| - Tensile Strength: | 95 – 165 kg/cm ² |
| - Temperature Limit: | -240 / +260°C |
| - Pressure Limit: | 690 BAR |
| | 700 BAR (Hydraulic) |
| - pH Range: 0 – | 14 |
| - Packaging: | 36 Units / Pack |

TPM MÜHENDİSLİK ENDÜSTRİ MALZEMELERİ SAN. TİC. LTD. ŞTİ.

Küçükyalı İş Merkezi C Blok No : 6 – 34852 Küçükyalı - MALTEPE / İSTANBUL

TEL: 0 216 549 26 27 – 3 Hat

Fax : 0 216 549 26 17

e-mail: tpm@tpm.com.tr

website: www.tpm.com.tr